



304 NORTH 35<sup>TH</sup> AVE  
P.O. BOX 1341  
PARAGOULD, ARKANSAS 72451

MONDAY - FRIDAY  
7:00 AM - 5:00 PM

PHONE (870) 236-8534 • FAX (870) 236-2829

**1-800-662-9841**

[www.steel-yard.com](http://www.steel-yard.com)

# Contents

<b>Item</b>	<b>Pages</b>
Angles .....	3-5
Steel.....	<u>3-4</u>
Aluminum, Stainless, Galvanized .....	<u>5</u>
Beams .....	6-9
I-Beams.....	<u>6</u>
Wide Flange.....	<u>7-9</u>
Channels .....	<u>10-11</u>
DOM Seamless Round Tubing .....	<u>12</u>
Expanded Metal .....	<u>13-14</u>
Flat Bars .....	15-20
Hot Roll.....	<u>15-16</u>
Cold Roll .....	<u>17-19</u>
Aluminum.....	<u>20</u>
Stainless.....	<u>19</u>
Round Bars .....	<u>21-22</u>
Square & Hexagon Bars.....	<u>23</u>
Pipe .....	24-26
Schedule 40 .....	<u>24-25</u>
Schedule 80 & Additional Large Pipe .....	<u>26</u>
Round Tubing .....	<u>27</u>
Square Tubing .....	<u>28-29</u>
Rectangular Tubing .....	<u>30-31</u>
Sheets & Plates.....	32-37
Aluminum.....	<u>35</u>
Galvanized .....	<u>37</u>
Mild Steel .....	<u>32-34</u>
Stainless.....	<u>36</u>
Tread Plates.....	<u>38</u>
Perforated, Woven & Welded Sheets.....	<u>39</u>
Rebar & Rewire .....	<u>39</u>
Bar Grating & Grip Strut.....	<u>40</u>

STEEL ANGLE					
Type		Wall Thickness		Weight per Foot (lbs)	
Width	Flange	In.	Dec.		
1/2	x 1/2	1/8	0.125	0.38	
3/4	x 3/4	1/8	0.125	0.59	
1	x 1	1/8	0.125	0.80	
		3/16	0.188	1.16	
		1/4	0.250	1.49	
1-1/4	x 1-1/4	1/8	0.125	1.01	
		3/16	0.188	1.48	
		1/4	0.250	1.92	
1-1/2	x 1-1/2	1/8	0.125	1.23	
		3/16	0.188	1.80	
		1/4	0.250	2.34	
1-3/4	x 1-3/4	1/8	0.125	1.44	
		3/16	0.188	2.12	
		1/4	0.250	2.77	
2	x 1-1/2	1/8	0.125	1.44	
		3/16	0.188	2.12	
		1/4	0.250	2.77	
2	x 2	1/8	0.125	1.65	
		3/16	0.188	2.44	
		1/4	0.250	3.19	
		5/16	0.313	3.92	
		3/8	0.375	4.70	
2-1/2	x 1-1/2	3/16	0.188	2.44	
		1/4	0.250	3.19	
2-1/2	x 2	3/16	0.188	2.75	
		1/4	0.250	3.62	
		5/16	0.313	4.50	
		3/8	0.375	5.30	
2-1/2	x 2-1/2	3/16	0.188	3.07	
		1/4	0.250	4.10	
		5/16	0.313	5.00	
		3/8	0.375	5.90	
		1/2	0.500	7.70	
3	x 2	3/16	0.188	3.07	
		1/4	0.250	4.10	
		5/16	0.313	5.00	
		3/8	0.375	5.90	
		1/2	0.500	7.70	
3	x 2-1/2	3/16	0.188	3.30	
		1/4	0.250	4.50	
		5/16	0.313	5.60	
		3/8	0.375	6.60	
		1/2	0.500	8.50	

STEEL ANGLE (Continued)					
Type		Wall Thickness		Weight per Foot (lbs)	
Width	Flange	In.	Dec.		
3	x 3	3/16	0.188	3.71	
		1/4	0.250	4.90	
		5/16	0.313	6.10	
		3/8	0.375	7.20	
		1/2	0.500	9.40	
3-1/2	x 2-1/2	1/4	0.250	4.90	
		5/16	0.313	6.10	
		3/8	0.375	7.20	
		1/2	0.500	9.40	
3-1/2	x 3	1/4	0.250	5.40	
		5/16	0.313	6.60	
		3/8	0.375	7.90	
		1/2	0.500	10.20	
3-1/2	x 3-1/2	1/4	0.250	5.80	
		5/16	0.313	7.20	
		3/8	0.375	8.50	
		1/2	0.500	11.10	
4	x 3	1/4	0.250	5.80	
		5/16	0.313	7.20	
		3/8	0.375	8.50	
		1/2	0.500	11.10	
		5/8	0.625	13.60	
4	x 4	1/4	0.250	6.60	
		5/16	0.313	8.20	
		3/8	0.375	9.80	
		1/2	0.500	12.80	
		5/8	0.625	15.70	
		3/4	0.750	18.50	
5	x 3	1/4	0.250	6.60	
		5/16	0.313	8.20	
		3/8	0.375	9.80	
		1/2	0.500	12.80	
5	x 5	5/16	0.313	10.30	
		3/8	0.375	12.30	
		1/2	0.500	16.20	
		3/4	0.750	23.60	
6	x 3-1/2	5/16	0.313	9.80	
		3/8	0.375	11.70	
		1/2	0.500	15.30	
6	x 4	5/16	0.313	10.30	
		3/8	0.375	12.30	
		1/2	0.500	16.20	
		5/8	0.625	20.00	
		3/4	0.750	23.60	

**STEEL ANGLE (Continued)**

Type		Wall Thickness		Weight per Foot (lbs)	
Width	Flange	In.	Dec.		
6	x	6	5/16	0.313	12.50
			3/8	0.375	14.90
			1/2	0.500	19.60
			5/8	0.625	24.20
			3/4	0.750	28.70
7	x	4	3/8	0.375	13.60
			1/2	0.500	17.90
8	x	4	1/2	0.500	19.60
			3/4	0.750	28.70
8	x	6	1/2	0.500	23.00
			5/8	0.625	28.50
			3/4	0.750	33.80
			1	1.000	44.20
8	x	8	1/2	0.500	26.40
			3/4	0.750	38.90
			1	1.000	51.00

STAINLESS ANGLE					
Type		Wall Thickness		Weight per Foot (lbs)	
Width	Flange	In.	Dec.		
3/4	x 3/4	1/8	0.125	0.590	
1	x 1	1/8	0.125	0.800	
		3/16	0.188	1.160	
		1/4	0.250	1.490	
1-1/4	x 1-1/4	1/8	0.125	1.010	
		3/16	0.188	1.480	
		1/4	0.250	1.920	
1-1/2	x 1-1/2	1/8	0.125	1.230	
		3/16	0.188	1.800	
		1/4	0.250	2.340	
2	x 2	1/8	0.125	1.650	
		3/16	0.188	2.440	
		1/4	0.250	3.190	
		3/8	0.375	4.700	
2-1/2	x 2-1/2	3/16	0.188	3.070	
		1/4	0.250	4.100	
		3/8	0.375	5.900	
3	x 2	3/16	0.188	3.070	
		1/4	0.250	4.100	
3	x 3	1/4	0.250	4.900	
		5/16	0.313	6.100	
4	x 4	1/4	0.250	6.600	
4	x 4	3/8	0.375	9.800	

ALUMINUM ANGLE					
Type		Wall Thickness		Weight per Foot (lbs)	
Width	Flange	In.	Dec.		
3/4	x 3/4	1/8	0.125	0.201	
1	x 1	1/8	0.125	0.270	
		3/16	0.188	0.400	
		1/4	0.250	0.510	
1-1/4	x 1-1/4	1/8	0.125	0.350	
		3/16	0.188	0.510	
		1/4	0.250	0.660	
1-1/2	x 1-1/2	1/8	0.125	0.430	
		3/16	0.188	0.620	
		1/4	0.250	0.810	
2	x 2	1/8	0.125	0.570	
		3/16	0.188	0.840	
		1/4	0.250	1.110	
2-1/2	x 2-1/2	3/16	0.188	1.070	
		1/4	0.250	1.410	
3	x 2	3/16	0.188	1.070	
		1/4	0.250	1.400	
3	x 3	3/16	0.188	1.290	
		1/4	0.250	1.680	
4	x 4	1/4	0.250	2.280	
5	x 3	1/4	0.250	2.272	

GALVANIZED ANGLE					
Type		Wall Thickness		Weight per Foot (lbs)	
Width	Flange	In.	Dec.		
1-1/2	x 1-1/2	1/8	0.125	1.250	
		3/16	0.188	1.890	
2	x 2	1/8	0.125	1.782	
		3/16	0.188	2.635	
		1/4	0.250	3.445	
3	x 3	1/4	0.250	5.150	

STEEL I-BEAMS						
Type (Size x Lbs per Ft.)			Depth of Section (in.)	Flange Width (in.)	Flange Thickness (in.)	Web Thickness (in.)
3	x	5.7	3.000	2.330	0.260	0.170
	x	7.5	3.000	2.509	0.260	0.349
4	x	7.7	4.000	2.660	0.293	0.193
	x	9.5	4.000	2.796	0.293	0.326
5	x	10	5.000	3.000	0.326	0.214
	x	14.75	5.000	3.284	0.326	0.494
6	x	12-1/2	6.000	3.332	0.359	0.232
	x	17.25	6.000	3.565	0.359	0.465
7	x	15.3	7.000	3.662	0.392	0.252
	x	20	7.000	3.860	0.392	0.450
8	x	18.4	8.000	4.001	0.425	0.271
	x	23	8.000	4.171	0.425	0.441
10	x	25.4	10.000	4.661	0.491	0.311
	x	35	10.000	4.944	0.491	0.594
12	x	31.8	12.000	5.000	0.544	0.350
	x	35	12.000	5.078	0.544	0.428
	x	40.8	12.000	5.252	0.659	0.462
	x	50	12.000	5.477	0.659	0.687
15	x	42.9	15.000	5.501	0.622	0.411
	x	50	15.000	5.640	0.622	0.550

## STEEL WIDE FLANGE BEAMS

Type (Size x Lbs per Ft.)			Depth of Section (in.)	Flange Width (in.)	Flange Thickness (in.)	Web Thickness (in.)
4	x	13	4.160	4.060	0.345	0.280
5	x	16	5.010	5.000	0.360	0.240
	x	19	5.150	5.030	0.430	0.200
6	x	9	5.900	3.940	0.125	0.170
	x	12	6.030	4.000	0.280	0.230
	x	15	5.990	5.990	0.260	0.230
	x	20	6.200	6.020	0.365	0.260
	x	25	6.380	6.080	0.455	0.320
8	x	10	7.890	3.940	0.205	0.170
	x	13	7.990	4.000	0.255	0.230
	x	15	8.110	4.015	0.315	0.245
	x	18	8.140	5.250	0.330	0.230
	x	21	8.280	5.270	0.400	0.250
	x	24	7.930	6.495	0.400	0.245
	x	28	8.060	6.350	0.465	0.285
	x	31	8.000	7.995	0.435	0.285
	x	35	8.120	8.020	0.495	0.310
	x	40	8.250	8.070	0.560	0.360
	x	48	8.500	8.110	0.685	0.400
	x	58	8.750	8.220	0.810	0.510
	x	67	9.000	8.280	0.935	0.570
10	x	12	9.870	3.960	0.210	0.190
	x	15	9.990	4.000	0.270	0.230
	x	17	10.110	4.010	0.330	0.240
	x	19	10.240	4.020	0.395	0.250
	x	22	10.170	5.750	0.360	0.240
	x	26	10.330	5.770	0.440	0.260
	x	30	10.470	5.810	0.510	0.300
	x	33	9.730	7.960	0.435	0.290
	x	39	9.920	7.985	0.530	0.315
	x	45	10.100	8.020	0.620	0.350
	x	49	9.980	10.000	0.560	0.340
	x	54	10.090	10.030	0.615	0.370
	x	60	10.220	10.080	0.680	0.420
12	x	14	11.910	3.970	0.225	0.200
	x	16	11.990	3.990	0.265	0.220
	x	19	12.160	4.005	0.350	0.235
	x	22	12.310	4.030	0.425	0.260
	x	26	12.220	6.490	0.380	0.230
	x	30	12.340	6.520	0.440	0.260
	x	35	12.500	6.560	0.520	0.300
	x	40	11.940	8.005	0.515	0.295
	x	45	12.060	8.045	0.575	0.335
	x	50	12.190	8.080	0.640	0.370
	x	53	12.060	9.995	0.575	0.345
	x	58	12.190	10.010	0.640	0.360

**STEEL WIDE FLANGE BEAMS**

Type (Size x Lbs per Ft.)			Depth of Section (in.)	Flange Width (in.)	Flange Thickness (in.)	Web Thickness (in.)
14	x	22	13.740	5.000	0.335	0.230
	x	26	13.910	5.025	0.420	0.255
	x	30	13.840	6.730	0.385	0.270
	x	34	13.980	6.745	0.455	0.285
	x	38	14.100	6.770	0.515	0.310
	x	43	13.660	7.995	0.530	0.305
	x	48	13.790	8.030	0.595	0.340
	x	53	13.920	8.060	0.660	0.370
	x	61	13.890	9.995	0.645	0.375
	x	68	14.040	10.350	0.720	0.415
	x	74	14.170	10.070	0.785	0.450
	x	82	14.310	10.130	0.855	0.510
16	x	26	15.690	5.500	0.345	0.250
	x	31	15.880	5.525	0.440	0.275
	x	36	15.860	6.985	0.430	0.295
	x	40	16.010	6.995	0.505	0.305
	x	45	16.130	7.035	0.565	0.345
	x	50	16.260	7.070	0.630	0.380
	x	57	16.430	7.120	0.715	0.430
	x	67	16.330	10.235	0.665	0.395
	x	77	16.520	10.295	0.760	0.455
	x	89	16.750	10.365	0.875	0.525
	x	100	16.970	10.425	0.985	0.585
18	x	35	17.700	6.000	0.425	0.300
	x	40	17.900	6.015	0.525	0.315
	x	46	18.060	6.060	0.605	0.360
	x	50	17.990	7.495	0.570	0.355
	x	55	18.110	7.530	0.630	0.390
	x	60	18.240	7.555	0.695	0.415
	x	65	18.350	7.590	0.750	0.450
	x	71	18.470	7.635	0.810	0.495
	x	76	18.210	11.035	0.680	0.425
	x	86	18.390	11.090	0.770	0.480
	x	97	18.590	11.145	0.870	0.535
	x	106	18.730	11.200	0.940	0.590
	x	119	18.970	11.265	1.060	0.655
21	x	44	20.660	6.500	0.450	0.350
	x	50	20.830	6.530	0.535	0.380
	x	57	21.060	6.555	0.650	0.405
	x	62	20.990	8.240	0.615	0.400
	x	68	21.130	8.270	0.685	0.430
	x	73	21.240	8.295	0.740	0.455
	x	83	21.430	8.355	0.835	0.515
	x	93	21.620	8.420	0.930	0.580
	x	101	21.360	12.290	0.800	0.500
	x	111	21.510	12.340	0.875	0.550
	x	122	21.680	12.390	0.960	0.600
	x	132	21.830	12.440	1.035	0.650
	x	147	22.060	12.510	1.150	0.720

**STEEL WIDE FLANGE BEAMS**

<b>Type</b>			<b>Depth of Section</b>	<b>Flange</b>	<b>Flange Thickness</b>	<b>Web Thickness</b>
<b>(Size x Lbs per Ft.)</b>			<b>(in.)</b>	<b>Width (in.)</b>	<b>(in.)</b>	<b>(in.)</b>
24	x	55	23.570	7.005	0.505	0.395
	x	62	23.740	7.040	0.590	0.430
	x	68	23.730	8.965	0.585	0.415
	x	76	23.920	8.990	0.680	0.440
	x	84	24.100	9.020	0.770	0.470
	x	94	24.310	9.065	0.875	0.515
	x	104	24.060	12.750	0.750	0.500
	x	117	24.260	12.800	0.850	0.550
	x	131	24.480	12.855	0.960	0.605
	x	146	24.740	12.900	1.090	0.650
	x	162	25.000	12.955	1.220	0.705
27	x	84	26.710	9.960	0.640	0.460
	x	94	26.920	9.990	0.745	0.490
	x	102	27.090	10.015	0.830	0.515
	x	114	27.290	10.070	0.930	0.570
	x	146	27.380	13.965	0.975	0.605
	x	161	27.590	14.020	1.080	0.660
	x	178	27.810	14.085	1.190	0.725

CHANNEL IRON					
Type			Wall Thickness		Weight per Foot (lbs)
Width	Flange		In.	Dec.	
1	x	1/2	1/8	0.125	0.84
1-1/4	x	1/2	1/8	0.125	1.01
1-1/2	x	1/2	1/8	0.125	1.12
2	x	1/2	1/8	0.125	1.47
2	x	1	1/8	0.125	1.78
			3/16	0.188	2.57

C CHANNELS (STANDARD)						
Type			Depth of Section (in.)	Flange Width (in.)	Flange Thickness (in.)	Web Thickness (in.)
(Size x Lbs per Ft.)						
3	x	4.1	3.000	1.410	0.273	0.170
	x	5	3.000	1.498	0.273	0.258
	x	6	3.000	1.596	0.273	0.356
4	x	5.4	4.000	1.580	0.296	0.184
	x	7.25	4.000	1.721	0.296	0.321
5	x	6.7	5.000	1.750	0.320	0.190
	x	9	5.000	1.885	0.320	0.325
6	x	8.2	6.000	1.920	0.343	0.200
	x	10.5	6.000	2.034	0.343	0.314
	x	13	6.000	2.157	0.343	0.437
7	x	9.8	7.000	2.090	0.366	0.210
	x	14.75	7.000	2.299	0.366	0.419
8	x	11.5	8.000	2.260	0.390	0.220
	x	13.75	8.000	2.343	0.390	0.303
	x	18.75	8.000	25.270	0.390	0.487
9	x	13.4	9.000	2.433	0.413	0.233
10	x	15.3	10.000	2.600	0.436	0.240
	x	20	10.000	2.739	0.436	0.379
	x	25	10.000	2.886	0.436	0.526
	x	30	10.000	3.033	0.436	0.673
12	x	20.7	12.000	2.942	0.501	0.282
	x	25	12.000	3.047	0.501	0.387
15	x	33.9	15.000	3.400	0.650	0.400

**MC CHANNELS (SHIP AND CAR)**

Type (Size x Lbs per Ft.)			Depth of Section (in.)	Flange Width (in.)	Flange Thickness (in.)	Web Thickness (in.)
3	x	7.1	2.930	1.938	0.351	0.312
4	x	13.8	4.000	2.500	0.500	0.500
6	x	12	6.000	2.497	0.375	0.310
	x	15.1	6.000	2.941	0.475	0.316
	x	15.3	6.000	3.500	0.385	0.340
	x	16.3	6.000	3.000	0.475	0.375
8 (Jr)	x	8.5	8.000	1.874	0.311	0.179
	x					
8	x	18.7	8.000	2.978	0.500	0.353
	x	20	8.000	3.025	0.500	0.400
10 (Jr)	x	8.4	10.000	1.500	0.280	0.170
	x					
10	x	33.6	10.000	4.100	0.575	0.575
12 (Jr)	x	10.6	12.000	1.500	0.309	0.190
	x					
18	x	42.7	18.000	3.950	0.625	0.450

## DOM SEAMLESS ROUND TUBING

O.D. (Inches)	I.D. (Inches)	O.D. (Dec.)	I.D. (Dec.)	Wall Thickness	
				Ga.	Dec.
1/2	1/4	0.50	0.25	11ga	0.125
3/4	3/8	0.75	0.38	3/16	0.188
3/4	1/2	0.75	0.51	11ga	0.120
1	1/2	1.00	0.50	1/4	0.250
1-1/4	3/4	1.25	0.75	1/4	0.250
1-1/4	1	1.25	1.00	11ga	0.125
1-1/4	1	1.25	1.01	11ga	0.120
1-1/2	3/4	1.50	0.75	3/8	0.375
1-1/2	1	1.50	1.00	1/4	0.250
1-1/2	1-1/4	1.50	1.26	11ga	0.120
1-3/4	1-1/4	1.75	1.25	1/4	0.250
1-3/4	1-1/2	1.75	1.50	11ga	0.125
2	1-1/2	2.00	1.50	1/4	0.250
2	1-3/4	2.00	1.76	11ga	0.120
2-1/4	1-1/4	2.25	1.25	1/2	0.500
2-1/4	1-3/4	2.25	1.75	1/4	0.250
2-1/2	1-1/2	2.50	1.50	1/2	0.500
2-1/2	2	2.50	2.00	1/4	0.250
2-1/2	2-1/4	2.50	2.26	11ga	0.120
2-3/4	2-1/4	2.75	2.25	1/4	0.250
3	1	3.00	1.00	1	1.000
3	2	3.00	2.00	1/2	0.500
3-1/2	2	3.50	2.00	3/4	0.750
3-1/2	3	3.50	3.00	1/4	0.250
4	3	4.00	3.00	1/2	0.500
4-1/2	3	4.50	3.00	3/4	0.750
4-3/4	3-3/4	4.75	3.75	1/2	0.500
5	3	5.00	3.00	1	1.000
5-1/2	4-1/2	5.50	4.50	1/2	0.500
6	5	6.00	5.00	1/2	0.500
6-1/2	5-1/2	6.50	5.50	1/2	0.500
7	6	7.00	6.00	1/2	0.500
8	7	8.00	7.00	1/2	0.500

Please note, our DOM tubing is available in a very wide range of sizes.

Listed here are only a few of our most commonly requested.

A number of other options are frequently stocked; with even more available for special order upon request.

## EXPANDED METAL (RAISED)

Type	Diamond Size		Thickness (in.)	Decimal Avg	Sheet Size		Weight per sq. foot	Weight per sheet
	Width	Length			Width	Length		
1/2" #16 Raised	0.375	0.938	16ga	0.065	48	96	0.86	27.52
1/2" #13 Raised	0.312	0.938	13ga	0.095	48	96	1.47	47.04
3/4" #16 Raised	0.813	1.750	16ga	0.065	48	96	0.54	17.28
3/4" #13 Raised	0.750	1.688	13ga	0.095	48	96	0.80	25.60
3/4" #9 Raised	0.688	1.562	9ga	0.156	48	96	1.80	57.60
					48	120	1.80	72.00
					48	144	1.80	86.40
					60	96	1.80	72.00
					60	120	1.80	90.00
					60	144	1.80	108.00
					72	120	1.80	108.00
					72	144	1.80	129.60
1-1/2" #9 Raised	1.125	2.375	9ga	0.156	48	96	1.20	38.40
1-1/2" #6 Raised	1.000	2.313	6ga	0.203	48	96	2.50	80.00
					60	120	2.50	125.00
#3 Exp Metal Grate	0.938	3.438	3/16	0.188	48	96	3.00	96.00
#4 Exp Metal Grate	0.938	3.438	1/4	0.250	48	96	4.00	128.00
					48	120	4.00	160.00

## EXPANDED METAL (FLATTENED)

Type	Diamond Size		Thickness (in.)	Decimal Avg	Sheet Size		Weight per sq. foot	Weight per sheet
	Width	Length			Width	Length		
1/4" #18 Flat	0.188	0.715	18ga	0.050	48	96	1.12	35.84
1/2" #16 Flat	0.312	1.000	16ga	0.065	48	96	0.82	26.24
					48	120	0.82	32.80
1/2" #13 Flat	0.265	1.000	13ga	0.095	48	96	1.40	44.80
					60	120	1.40	70.00
3/4" #16 Flat	0.750	1.750	16ga	0.065	48	96	0.54	17.28
3/4" #13 Flat	0.688	1.781	13ga	0.095	48	96	0.75	24.00
					48	120	0.75	30.00
3/4" #9 Flat	0.563	1.688	9ga	0.156	48	96	1.71	54.72
					48	120	1.71	68.40
					48	144	1.71	82.08
					60	120	1.71	85.50
1-1/2" #13 Flat	1.062	2.750	13ga	0.095	48	96	0.57	18.24
1-1/2" #9 Flat	1.000	2.563	9ga	0.156	48	96	1.14	36.48
1-1/2" #6 Flat	1.000	2.500	6ga	0.203	48	96	2.41	77.12

## ALUMINUM EXPANDED METAL

Type	Diamond Size		Thickness (in.)	Decimal Avg	Sheet Size		Weight per sq. foot	Weight per sheet
	Width	Length			Width	Length		
1/2" #14 Flat	0.265	1.000	14ga	0.081	48	96	0.44	14.08
3/4" #11 Flat	0.563	1.688	11ga	0.125	48	96	0.65	20.80

## STAINLESS EXPANDED METAL

Type	Diamond Size		Thickness (in.)	Decimal Avg	Sheet Size		Weight per sq. foot	Weight per sheet
	Width	Length			Width	Length		
1/2" #16 Flat	0.312	1.000	16ga	0.065	48	96	0.70	22.40
3/4" #9 Raised	0.563	1.688	9ga	0.156	48	96	2.05	65.60

HOT ROLL FLAT BAR (A36)			
Size		Weight per Foot (lbs)	Weight per Stick
Thickness	Width		
1/8	1/2	0.213	2.556
	3/4	0.319	3.828
	1	0.425	5.100
	1 1/4	0.531	6.372
	1 1/2	0.638	7.656
	1 3/4	0.744	8.928
	2	0.850	10.200
	2 1/2	1.063	12.756
	3	1.275	15.300
	4	1.700	20.400
	5	2.125	25.500
	6	2.550	30.600
3/16	1/2	0.319	3.828
	3/4	0.478	5.736
	1	0.638	7.656
	1 1/4	0.797	9.564
	1 1/2	0.956	11.472
	1 3/4	1.116	13.392
	2	1.275	15.300
	2 1/2	1.594	19.128
	3	1.913	22.956
	3 1/2	2.231	26.772
	4	2.550	30.600
	5	3.188	38.256
6	3.825	45.900	
1/4	1/2	0.425	5.100
	3/4	0.638	7.650
	1	0.850	10.200
	1 1/4	1.063	12.750
	1 1/2	1.275	15.300
	1 3/4	1.488	17.856
	2	1.700	20.400
	2 1/2	2.125	25.500
	3	2.550	30.600
	3 1/2	2.975	35.700
	4	3.400	40.800
	4 1/2	3.825	45.900
5	4.250	51.000	
6	5.100	61.200	
8	6.800	81.600	
10	8.500	102.000	
12	10.200	122.400	
5/16	3/4	0.797	9.563
	1	1.625	19.500
	1 1/4	1.328	15.937
	1 1/2	1.594	19.128
	2	2.125	25.500
	2 1/2	2.656	31.872
	3	0.319	3.826
	3 1/2	3.719	44.628
5	5.313	63.756	
6	6.375	76.500	

HOT ROLL FLAT BAR (A36)			
Size		Weight per Foot (lbs)	Weight per Stick
Thickness	Width		
3/8	1/2	0.638	7.650
	3/4	0.956	11.476
	1	1.275	15.300
	1 1/4	1.594	19.126
	1 1/2	1.913	22.956
	1 3/4	2.231	26.772
	2	2.550	30.600
	2 1/2	3.188	38.256
	3	3.825	45.900
	3 1/2	4.463	53.556
	4	5.100	61.200
	5	6.375	76.500
6	7.650	91.800	
7	8.930	107.160	
8	10.200	122.400	
9	11.480	137.760	
10	12.750	153.000	
12	15.300	183.600	
1/2	3/4	1.275	15.300
	1	1.700	20.400
	1 1/4	2.125	25.500
	1 1/2	2.550	30.600
	1 3/4	2.975	35.700
	2	3.400	40.800
	2 1/2	4.250	51.000
	3	5.100	61.200
	3 1/2	5.950	71.400
	4	6.800	81.600
	4 1/2	7.650	91.800
	5	8.500	102.000
5 1/2	9.350	112.200	
6	10.200	122.400	
7	11.900	142.800	
8	13.600	163.200	
9	15.300	183.600	
10	17.000	204.000	
12	20.400	244.800	
5/8	1	2.125	25.500
	1 1/2	3.188	38.256
	2	4.250	51.000
	3	6.375	76.500
	4	8.500	102.000
	5	10.625	127.500
	6	12.750	153.000
	8	17.080	204.960
12	25.500	306.000	

HOT ROLL FLAT BAR (A36)				
Size		Weight per Foot (lbs)	Weight per Stick	
Thickness	Width			
3/4	1	2.550	30.600	
	1 1/4	3.188	38.256	
	1 1/2	3.825	45.900	
	1 3/4	4.463	53.556	
	2	5.100	61.200	
	2 1/2	6.375	76.500	
	2 3/4	7.013	84.156	
	3	7.650	91.800	
	3 1/2	8.925	107.100	
	4	10.200	122.400	
	4 1/2	11.475	137.700	
	5	12.750	153.000	
	6	15.300	183.600	
7/8	7	17.850	214.200	
	8	20.400	244.800	
	10	25.500	306.000	
	11	28.050	336.600	
	12	30.600	367.200	
	4	11.900	142.800	
	1	1 1/4	4.250	51.000
		1 1/2	5.100	61.200
		2	6.800	81.600
		2 1/2	8.500	102.000
		3	10.200	122.400
		4	13.600	163.200
		4 1/2	15.300	183.600
5		17.000	204.000	
6		20.400	244.800	
7		23.800	285.600	
8		27.200	326.400	
10		34.000	408.000	
12		40.800	489.600	
1-1/4	2	8.500	102.000	
	2 1/2	10.625	127.500	
	3	12.750	153.000	
	4	17.000	204.000	
	5	21.250	255.000	
1-1/2	2	10.200	122.400	
	2 1/2	12.750	153.000	
	3	15.300	183.600	
	4	20.400	244.800	
	5	25.500	306.000	
	6	30.600	367.200	
2	3	20.400	244.800	
	4	27.200	326.400	
	5	34.000	408.000	
	6	40.800	489.600	
2-1/2	4	34.032	408.384	

COLD ROLL FLAT BAR (1018)			
Size		Weight per Foot (lbs)	Weight per Stick
Thickness	Width		
1/8	1/4	0.106	1.272
	3/8	0.159	1.908
	1/2	0.213	2.556
	5/8	0.266	3.192
	3/4	0.319	3.828
	7/8	0.372	4.464
	1	0.425	5.100
	1 1/4	0.531	6.372
	1 1/2	0.638	7.656
	1 3/4	0.744	8.928
	2	0.850	10.200
	2 1/4	0.956	11.472
	2 1/2	1.063	12.756
	2 3/4	1.169	14.028
	3	1.275	15.300
	4	1.700	20.400
	5	2.125	25.500
5 1/2	2.338	28.056	
6	2.550	30.600	
3/16	1/4	0.159	1.913
	3/8	0.239	2.868
	1/2	0.319	3.828
	3/4	0.478	5.736
	1	0.638	7.656
	1 1/4	0.797	9.564
	1 1/2	0.956	11.472
	1 3/4	1.116	13.392
	2	1.275	15.300
	2 1/4	1.434	17.208
	2 1/2	1.594	19.128
	3	1.913	22.956
	3 1/2	2.231	26.772
	4	2.550	30.600
	5	3.188	38.256
	6	3.825	45.900
	1/4	3/8	0.319
1/2		0.425	5.100
9/16		0.480	5.760
5/8		0.531	6.376
3/4		0.638	7.650
1		0.850	10.200
1 1/4		1.063	12.750
1 3/8		1.169	14.028
1 1/2		1.275	15.300
1 3/4		1.488	17.856
2		1.700	20.400
2 1/4		1.913	22.956
2 1/2		2.125	25.500
3		2.550	30.600
3 1/2		2.975	35.700
4		3.400	40.800
4 1/2		3.825	45.900
5	4.250	51.000	

COLD ROLL FLAT BAR (1018)			
Size		Weight per Foot (lbs)	Weight per Stick
Thickness	Width		
1/4	6	5.100	61.200
	8	6.800	81.600
	10	8.500	102.000
	12	10.200	122.400
5/16	3/4	0.797	9.563
	1	1.625	19.500
	1 1/4	1.328	15.937
	1 3/8	1.461	17.532
	1 1/2	1.594	19.128
	2	2.125	25.500
	2 1/4	2.391	28.692
	2 1/2	2.656	31.872
	3	0.319	3.826
	3 1/2	3.719	44.628
	4	4.250	51.000
5	5.313	63.756	
6	6.375	76.500	
3/8	7/16	0.558	6.694
	1/2	0.638	7.650
	5/8	0.797	9.563
	3/4	0.956	11.476
	7/8	1.116	13.387
	1	1.275	15.300
	1 1/4	1.594	19.126
	1 3/8	1.753	21.036
	1 1/2	1.913	22.956
	1 3/4	2.231	26.772
	2	2.550	30.600
	2 1/4	2.869	34.428
	2 1/2	3.188	38.256
	2 3/4	3.506	42.072
	3	3.825	45.900
	3 1/4	4.144	49.728
	3 1/2	4.463	53.556
4	5.100	61.200	
5	6.375	76.500	
6	7.650	91.800	
7	8.930	107.160	
8	10.200	122.400	
9	11.480	137.760	
10	12.750	153.000	
12	15.300	183.600	
1/2	9/16	0.956	11.476
	5/8	1.063	12.756
	3/4	1.275	15.300
	7/8	1.488	17.856
	1	1.700	20.400
	1 1/8	1.913	22.956
	1 1/2	2.550	30.600
	1 3/4	2.975	35.700
	2	3.400	40.800
	2 1/4	38.250	459.000
	2 1/2	4.250	51.000
2 3/4	4.675	56.100	

COLD ROLL FLAT BAR (1018)			
Size		Weight per Foot (lbs)	Weight per Stick
Thickness	Width		
1/2	3	5.100	61.200
	3 1/4	5.525	66.300
	3 1/2	5.950	71.400
	4	6.800	81.600
	4 1/2	7.650	91.800
	5	8.500	102.000
	5 1/2	9.350	112.200
	6	10.200	122.400
	8	13.600	163.200
	10	17.000	204.000
	11	18.700	224.400
	12	20.400	244.800
5/8	3/4	1.594	19.128
	1	2.125	25.500
	1 1/4	2.656	31.872
	1 1/2	3.188	38.256
	1 3/4	3.719	44.628
	2	4.250	51.000
	2 1/4	4.781	57.372
	2 1/2	5.313	63.756
	3	6.375	76.500
	3 1/2	7.438	89.256
	4	8.500	102.000
	4 1/2	9.563	114.756
5	10.625	127.500	
6	12.750	153.000	
8	17.080	204.960	
12	25.500	306.000	
3/4	1	2.550	30.600
	1 1/4	3.188	38.256
	1 1/2	3.825	45.900
	1 3/4	4.463	53.556
	2	5.100	61.200
	2 1/2	6.375	76.500
	2 3/4	7.013	84.156
	3	7.650	91.800
	3 1/2	8.925	107.100
	4	10.200	122.400
	4 1/2	11.475	137.700
	5	12.750	153.000
5 1/2	14.025	168.300	
6	15.300	183.600	
6 1/2	16.575	198.900	
7	17.850	214.200	
8	20.400	244.800	
10	25.500	306.000	
11	28.050	336.600	
12	30.600	367.200	
7/8	1	2.975	35.700
	1 1/2	4.463	53.556
	1 3/4	5.206	62.472
	2	5.950	71.400
	3	8.925	107.100

COLD ROLL FLAT BAR (1018)				
Size		Weight per Foot (lbs)	Weight per Stick	
Thickness	Width			
7/8	4	11.900	142.800	
	1	1 1/8	3.825	45.900
		1 1/4	4.250	51.000
		1 1/2	5.100	61.200
		1 3/4	5.950	71.400
		2	6.800	81.600
		2 1/4	7.650	91.800
		2 1/2	8.500	102.000
		2 3/4	9.350	112.200
		3	10.200	122.400
		3 1/2	11.900	142.800
		4	13.600	163.200
4 1/2		15.300	183.600	
5	17.000	204.000		
5 1/2	18.700	224.400		
6	20.400	244.800		
7	23.800	285.600		
8	27.200	326.400		
10	34.000	408.000		
12	40.800	489.600		
1-1/8	2	7.650	91.800	
	3	11.480	137.760	
	8	30.600	367.200	
1-1/4	1 1/2	6.375	76.500	
	1 3/4	7.438	89.256	
	2	8.500	102.000	
	2 1/2	10.625	127.500	
	3	12.750	153.000	
1-1/2	4	17.000	204.000	
	8	34.000	408.000	
	1 3/4	8.925	107.100	
	2	10.200	122.400	
1-3/4	2 1/2	12.750	153.000	
	3	15.300	183.600	
	3 1/2	17.850	214.200	
	4	20.400	244.800	
	4 1/2	22.950	275.400	
	5	25.500	306.000	
	5 1/2	28.050	336.600	
	6	30.600	367.200	
	7	35.700	428.400	
	8	40.800	489.600	
	9	45.940	551.280	
	10	51.000	612.000	
12	61.200	734.400		
1-3/4	2	11.900	142.800	
	2 1/2	14.880	178.560	
	3	17.850	214.200	
	4	23.800	285.600	
6	35.700	428.400		

<b>COLD ROLL FLAT BAR (1018)</b>			
<b>Size</b>		<b>Weight per Foot (lbs)</b>	<b>Weight per Stick</b>
<b>Thickness</b>	<b>Width</b>		
2	3	20.400	244.800
	4	27.200	326.400
	5	34.000	408.000
	6	40.800	489.600
	8	54.400	652.800
	12	81.600	979.200
3	4	40.800	489.600
	5	51.000	612.000
	6	61.200	734.400

<b>STAINLESS FLAT BAR (304)</b>				
<b>Size</b>		<b>Weight per Foot (lbs)</b>	<b>Weight per Stick</b>	
<b>Thickness</b>	<b>Width</b>			
1/8	1/2	0.213	2.556	
	3/4	0.319	3.828	
	1	0.425	5.100	
	1 1/4	0.531	6.372	
	1 1/2	0.638	7.656	
	2	0.850	10.200	
	3/16	3/4	0.478	5.736
		1	0.638	7.656
		1 1/2	0.956	11.472
		2	1.275	15.300
4		2.550	30.600	
1/4		1/2	0.425	5.100
	3/4	0.638	7.656	
	1	0.850	10.200	
	1 1/4	1.063	12.756	
	1 1/2	1.275	15.300	
	1 3/4	1.488	17.856	
	2	1.700	20.400	
	2 1/2	2.125	25.500	
	3	2.550	30.600	
	4	3.400	40.800	
	5	4.250	51.000	
	6	1.762	21.144	
3/8	1	1.275	15.300	
	1 1/4	1.594	19.128	
	1 1/2	1.913	22.956	
	2	2.550	30.600	
	2 1/2	3.188	38.256	
	3	3.825	45.900	
1/2	4	5.100	61.200	
	1	1.700	20.400	
	1 1/2	2.550	30.600	
	2	3.400	40.800	
	3	5.100	61.200	
	4	6.800	81.600	
	6	10.200	122.400	
	8	13.600	163.200	
3/4	1	2.550	30.600	
	1	1 1/2	5.100	61.200
2		6.800	81.600	
5		17.000	204.000	
1-1/2	2	10.200	122.400	
	2	4	27.200	326.400

ALUMINUM FLAT BAR (6061)			
Size		Weight per Foot (lbs)	Weight per Stick
Thickness	Width		
1/8	1/2	0.073	0.874
	3/4	0.110	1.318
	1	0.147	1.764
	1 1/2	0.222	2.658
	2	0.294	3.528
	3	0.441	5.292
	4	0.588	7.056
3/16	3/4	0.165	1.980
	1	0.220	2.640
	1 1/2	0.331	3.972
	2	0.441	5.292
	3	0.663	7.956
	4	0.882	10.584
1/4	1/2	0.147	1.764
	3/4	0.225	2.696
	1	0.294	3.528
	1 1/4	0.367	4.404
	1 1/2	0.441	5.292
	2	0.587	7.044
	3	0.881	10.572
	4	1.141	13.692
	5	1.469	17.628
	6	1.762	21.144
3/8	1/2	0.220	2.640
	3/4	0.330	3.960
	1	0.441	5.292
	1 1/4	0.551	6.612
	1 1/2	0.625	7.500
	2	0.881	10.572
	2 1/2	1.123	13.476
	3	1.322	15.864
	4	1.762	21.144
	5	2.203	26.436
	6	2.643	31.716
	10	4.410	52.920
1/2	3/4	0.440	5.280
	1	0.587	7.044
	1 1/2	0.818	9.816
	1 3/4	1.029	12.348
	2	1.175	14.100
	2 1/2	1.469	17.628
	3	1.762	21.144
	4	2.350	28.200
	5	2.937	35.244
	6	3.524	42.288
	8	4.704	56.448
	10	5.880	70.560
	12	7.049	84.588

ALUMINUM FLAT BAR (6061)			
Size		Weight per Foot (lbs)	Weight per Stick
Thickness	Width		
3/4	1	0.880	10.560
	1 1/2	1.320	15.840
	2	1.762	21.144
	2 1/2	2.170	26.040
	3	2.533	30.396
	3 1/2	3.087	37.044
	4	3.522	42.264
	5	4.406	52.872
	6	5.292	63.504
	8	7.044	84.528
1	1 1/2	1.760	21.120
	2	2.350	28.200
	3	3.530	42.360
	4	4.700	56.400
	5	5.910	70.920
	6	7.056	84.672
	8	9.398	112.776
	12	14.080	168.960
1-1/4	2	2.937	35.244
	4	5.880	70.560
1-1/2	2	3.530	42.360
	3	5.287	63.444
	6	10.584	127.008
	8	14.112	169.344
2	3	7.056	84.672
	4	9.398	112.776
	6	14.100	169.200

<b>COLD ROLL ROUND (1018)</b>		
<b>Size</b>		<b>Weight per Foot (lbs)</b>
<b>In.</b>	<b>Dec.</b>	
1/8	0.125	0.042
3/16	0.188	0.094
1/4	0.250	0.167
5/16	0.313	0.261
3/8	0.375	0.376
7/16	0.438	0.511
1/2	0.500	0.668
9/16	0.563	0.845
5/8	0.625	1.043
11/16	0.688	1.262
3/4	0.750	1.502
13/16	0.813	1.763
7/8	0.875	2.045
15/16	0.938	2.347
1	1.000	2.670
1-1/16	1.063	3.015
1-1/8	1.125	3.380
1-3/16	1.188	3.766
1-1/4	1.250	4.172
1-5/16	1.313	4.600
1-3/8	1.375	5.049
1-7/16	1.438	5.518
1-1/2	1.500	6.008
1-5/8	1.625	7.051
1-11/16	1.688	7.604
1-3/4	1.750	8.178
1-13/16	1.813	8.773
1-7/8	1.875	9.388
1-15/16	1.938	10.020
2	2.000	10.680
2-1/8	2.125	12.060
2-3/16	2.187	12.780
2-1/4	2.250	13.520
2-7/16	2.438	15.870
2-1/2	2.500	16.690
2-5/8	2.625	18.400
2-3/4	2.750	20.190
2-15/16	2.938	23.064
3	3.000	24.030
3-1/4	3.250	28.210
3-3/8	3.375	30.420
3-7/16	3.438	31.584
3-1/2	3.500	32.710
3-3/4	3.750	37.550
3-15/16	3.938	41.440
4	4.000	42.730
4-1/2	4.500	54.080
4-3/4	4.750	60.250
5	5.000	66.760
5-1/2	5.500	80.780
5-3/4	5.750	88.290
6	6.000	96.130

<b>COLD ROLL ROUND (OTHER)</b>		
<b>Size</b>		<b>Grade</b>
<b>In.</b>	<b>Dec.</b>	
3/8	0.375	4140A
1/2	0.500	4140A
3/4	0.750	4140A
7/8	0.875	4140A
1	1.000	4140A
1-1/4	1.250	4140A
1-3/8	1.375	4140A
1-1/2	1.500	4140A
1-5/8	1.625	4140A
1-3/4	1.750	4140A
1-15/16	1.938	4140A
2	2.000	4140A
2-1/8	2.125	4140A
2-15/16	2.938	4140A
4	4.000	4140A
1/2	0.500	4140HT
5/8	0.625	4140HT
3/4	0.750	4140HT
1	1.000	4140HT
1-7/16	1.438	4140HT
1-1/2	1.500	4140HT
1-3/4	1.750	4140HT
2	2.000	4140HT
1/2	0.500	1144 SP
9/16	0.563	1144 SP
5/8	0.625	1144 SP
3/4	0.750	1144 SP
1	1.000	1144 SP
1-1/4	1.250	1144 SP
1-7/16	1.438	1144 SP
1-1/2	1.500	1144 SP
1-3/4	1.750	1144 SP
2	2.000	1144 SP
2-1/2	2.500	1144 SP
3-1/2	3.500	1144 SP
3/4	0.750	12L14
1	1.000	12L14
1-3/8	1.375	12L14
1-1/2	1.500	12L14
7/8	0.875	1141
1	1.000	1045
1-1/4	1.250	1045
1-1/2	1.500	1045
1-5/8	1.625	1045
2	2.000	1045
3	3.000	1045
3-1/2	3.500	1045
4	4.000	1045

<b>HOT ROLL ROUND (A36)</b>		
<b>Size</b>		<b>Weight per Foot (lbs)</b>
<b>In.</b>	<b>Dec.</b>	
1/4	0.250	0.167
5/16	0.313	0.261
3/8	0.375	0.376
7/16	0.438	0.511
1/2	0.500	0.668
5/8	0.625	1.043
3/4	0.750	1.502
7/8	0.875	2.045
1	1.000	2.670
1-1/4	1.250	4.172
1-3/8	1.375	5.049
1-1/2	1.500	6.008
1-3/4	1.750	8.178
2	2.000	10.680
2-1/2	2.500	16.690
2-3/4	2.750	20.190
2-7/8	2.875	22.070
3	3.000	24.030
3-1/2	3.500	32.710

<b>HOT ROLL ROUND (1018)</b>		
<b>Size</b>		<b>Weight per Foot (lbs)</b>
<b>In.</b>	<b>Dec.</b>	
5	5.000	66.760
6	6.000	96.130
6-1/2	6.500	116.190
7	7.000	134.750
9	9.000	222.760
10	10.000	275.010
12	12.000	384.898

<b>HOT ROLL ROUND (OTHER)</b>		
<b>Size</b>		<b>Grade</b>
<b>In.</b>	<b>Dec.</b>	
2-1/4	2.250	4150HT
4-1/4	4 1/4	4140A
4-1/2	4 1/2	4140A
5	5	4140A
4-1/2	4.500	4340A
5	5.000	4140HT
6	6.000	4140HT
11	11.000	1045.000

<b>ALUMINUM ROUND (6061)</b>		
<b>Size</b>		<b>Weight per Foot (lbs)</b>
<b>In.</b>	<b>Dec.</b>	
3/16	0.188	0.032
1/4	0.250	0.058
3/8	0.375	0.130
1/2	0.500	0.231
5/8	0.625	0.360
3/4	0.750	0.519
7/8	0.875	0.706
1	1.000	0.923
1-1/4	1.250	1.440
1-3/8	1.375	1.740
1-7/16	1.438	1.900
1-1/2	1.500	2.080
1-5/8	1.625	2.440
1-3/4	1.750	2.820
2	2.000	3.690
2-1/4	2.250	4.670
2-3/8	2.375	5.420
2-1/2	2.500	5.770
2-3/4	2.750	6.980
3	3.000	8.300
4	4.000	14.760
4-1/2	4.500	18.680
5	5.000	23.070
6	6.000	33.220

<b>STAINLESS ROUND (304)</b>		
<b>Size</b>		<b>Weight per Foot (lbs)</b>
<b>In.</b>	<b>Dec.</b>	
1/8	0.125	0.042
3/16	0.188	0.094
1/4	0.250	0.167
5/16	0.313	0.261
3/8	0.375	0.376
7/16	0.438	0.511
1/2	0.500	0.668
9/16	0.563	0.845
5/8	0.625	1.043
3/4	0.750	1.502
7/8	0.875	2.045
1	1.000	2.670
1-1/4	1.250	4.172
1-1/2	1.500	6.008
1-3/4	1.750	8.178
2	2.000	10.680

<b>COLD ROLL SQUARE (1018)</b>		
<b>Size</b>		<b>Weight per Foot (lbs)</b>
<b>In.</b>	<b>Dec.</b>	
1/8	0.125	0.05
3/16	0.188	0.12
1/4	0.250	0.21
5/16	0.313	0.33
3/8	0.375	0.48
1/2	0.500	0.85
9/16	0.563	1.08
5/8	0.625	1.33
3/4	0.750	1.91
7/8	0.875	2.60
15/16	0.938	2.99
1	1.000	3.40
1-1/8	1.125	4.30
1-3/16	1.187	4.80
1-1/4	1.250	5.31
1-3/8	1.375	6.43
1-1/2	1.500	7.65
1-3/4	1.750	10.41
1-7/8	1.875	11.95
2	2.000	13.60
2-1/2	2.500	21.25
2-3/4	2.750	25.71
3	3.000	30.60
3-1/4	3.250	35.91
3-1/2	3.500	41.65
6	6.000	122.40

<b>ALUMINUM SQUARE (6061)</b>		
<b>Size</b>		<b>Weight per Foot (lbs)</b>
<b>In.</b>	<b>Dec.</b>	
1/2	0.500	0.29
3/4	0.750	0.66
1	1.000	1.18
1-1/4	1.250	1.84
1-1/2	1.500	2.65
1-3/4	1.750	3.60
2	2.000	4.70
2-1/4	2.250	4.99
2-1/2	2.500	7.35

<b>STAINLESS SQUARE (304)</b>		
<b>Size</b>		<b>Weight per Foot (lbs)</b>
<b>In.</b>	<b>Dec.</b>	
1/4	0.250	0.21
5/16	0.313	0.33
3/8	0.375	0.48
1/2	0.500	0.85
3/4	0.750	1.92
1	1.000	3.42
1-1/2	1.500	7.65

<b>COLD ROLL HEX BAR (1018)</b>		
<b>Size</b>		<b>Weight per Foot (lbs)</b>
<b>In.</b>	<b>Dec.</b>	
5/16	0.313	0.288
3/8	0.375	0.414
7/16	0.438	0.564
1/2	0.500	0.736
9/16	0.563	0.932
5/8	0.625	1.150
3/4	0.750	1.656
7/8	0.875	2.254
15/16	0.938	2.588
1	1.000	2.945
1-1/16	1.063	3.324
1-1/4	1.250	4.601
1-1/2	1.500	6.625
1-3/4	1.750	9.018
2-1/4	2.250	14.910
3	3.000	26.500

<b>HOT ROLL SQUARE (A36)</b>		
<b>Size</b>		<b>Weight per Foot (lbs)</b>
<b>In.</b>	<b>Dec.</b>	
3/8	0.375	0.48
1/2	0.500	0.85
5/8	0.625	1.33
3/4	0.750	1.91
1	1.000	3.40
1-1/4	1.250	5.31
1-1/2	1.500	7.65
2	2.000	13.60
2-1/2	2.500	21.25
3	3.000	30.60
3-1/2	3.500	41.65
4	4.000	54.40
6	6.000	122.40

**STEEL SCHEDULE 40 PIPE**

Size (nominal)	O.D. (Inches)	I.D. (Inches)	Wall Thick- ness	Weight per Foot (lbs)		Threads per Inch
				Plain Ends	T&C	
1/8	0.405	0.269	0.068	0.24	0.25	27
1/4	0.540	0.364	0.088	0.42	0.43	18
3/8	0.675	0.493	0.091	0.57	0.57	18
1/2	0.840	0.622	0.109	0.85	0.85	14
3/4	1.050	0.824	0.113	1.13	1.13	14
1	1.315	1.049	0.133	1.68	1.68	11 1/2
1-1/4	1.660	1.380	0.140	2.27	2.28	11 1/2
1-1/2	1.900	1.610	0.145	2.72	2.73	11 1/2
2	2.375	2.067	0.154	3.65	3.68	11 1/2
2-1/2	2.875	2.469	0.203	5.79	5.82	8
3	3.500	3.068	0.216	7.58	7.62	8
3-1/2	4.000	3.548	0.226	9.11	9.20	8
4	4.500	4.026	0.237	10.79	10.89	8
5	5.563	5.047	0.258	14.62	14.81	8
6	6.625	6.065	0.280	18.97	19.19	8
8	8.625	8.071	0.277	24.70	25.00	8
8	8.625	7.981	0.322	28.55	28.81	8
10	10.750	10.020	0.365	40.48	41.13	8
12	12.750	11.938	0.406	53.57		
14	14.000	13.124	0.438	63.37		

**GALVANIZED SCHEDULE 40 PIPE**

Size (nominal)	O.D. (Inches)	I.D. (Inches)	Wall Thick- ness	Weight per Foot (lbs)		Threads per Inch
				Plain Ends	T&C	
1/4	0.540	0.364	0.088	0.43		
1/2	0.840	0.622	0.109	0.85	0.85	14
3/4	1.050	0.824	0.113	1.13	1.13	14
1	1.315	1.049	0.133	1.68		
1-1/4	1.660	1.380	0.140	2.27		
1-1/2	1.900	1.610	0.145	2.72	2.73	11 1/2
2	2.375	2.067	0.154	3.65		
2-1/2	2.875	2.469	0.203	5.79		
3	3.500	3.068	0.216	7.58		
3-1/2	4.000	3.548	0.226	9.11		

**ALUMINUM SCHEDULE 40 PIPE**

Size (nominal)	O.D. (Inches)	I.D. (Inches)	Wall Thick- ness	Weight per Foot (lbs)
1/4	0.540	0.364	0.088	0.15
1/2	0.840	0.622	0.109	0.29
3/4	1.050	0.824	0.113	0.39
1	1.315	1.049	0.133	0.58
1-1/4	1.660	1.380	0.140	0.79
1-1/2	1.900	1.610	0.145	0.93
2	2.375	2.067	0.154	1.26
2-1/2	2.875	2.469	0.203	2.00
3	3.500	3.068	0.216	2.62
4	4.500	4.026	0.237	0.37

**STAINLESS SCHEDULE 40 PIPE**

Size (nominal)	O.D. (Inches)	I.D. (Inches)	Wall Thick- ness	Weight per Foot (lbs)
1/4	0.540	0.364	0.088	0.43
3/8	0.675	0.493	0.091	0.57
1/2	0.840	0.622	0.109	0.85
3/4	1.050	0.824	0.113	1.13
1	1.315	1.049	0.133	1.68
1-1/4	1.660	1.380	0.140	2.27
1-1/2	1.900	1.610	0.145	2.72
2	2.375	2.067	0.154	3.65
2-1/2	2.875	2.469	0.203	5.79
3	3.500	3.068	0.216	7.58
3-1/2	4.000	3.548	0.226	9.11
4	4.500	4.026	0.237	10.89

**STEEL SCHEDULE 80 PIPE**

Size (nominal)	O.D. (Inches)	I.D. (Inches)	Wall Thick- ness	Weight per Foot (lbs)		Threads per Inch
				Plain Ends	T&C	
1/4	0.540	0.302	0.119	0.54	0.54	18
3/8	0.675	0.423	0.126	0.74	0.75	18
1/2	0.840	0.546	0.147	1.09	1.10	14
3/4	1.050	0.742	0.154	1.48	1.49	14
1	1.315	0.957	0.179	2.17	2.20	11 1/2
1-1/4	1.660	1.278	0.191	3.00	3.05	11 1/2
1-1/2	1.900	1.500	0.200	3.63	3.69	11 1/2
2	2.375	1.939	0.218	5.03	5.15	11 1/2
2-1/2	2.875	2.323	0.276	7.67	7.83	8
3	3.500	2.900	0.300	10.26	10.46	8
3-1/2	4.000	3.364	0.318	12.52	12.82	8
4	4.500	3.826	0.337	15.00	15.39	8
5	5.563	4.813	0.375	20.80	21.42	8
6	6.625	5.761	0.432	28.60	29.33	8
8	8.625	7.625	0.500	43.43	44.72	8
10	10.750	9.564	0.593	64.39		
12	12.750	11.376	0.687	88.59		

**ADDITIONAL PIPE**

Size	Type	O.D. (Inches)	I.D. (Inches)	Wall Thick- ness	Weight per Foot (lbs)
10	Sched 20	10.750	10.250	0.250	28.06
	Sched 30	10.750	10.136	0.307	34.27
	X-Heavy	10.750	9.750	0.500	54.79
12	Sched 20	12.750	12.250	0.250	33.41
	Sched 30	12.750	12.090	0.330	43.81
	Standard	12.750	12.000	0.375	49.61
	X-Heavy	12.750	11.750	0.500	65.48
14	Sched 10	14.000	13.500	0.250	36.75
	Sched 20	14.000	13.376	0.312	45.65
	Sched 30	14.000	13.250	0.375	54.62
	X-Heavy	14.000	13.000	0.500	72.16
16	Sched 10	16.000	15.500	0.250	42.09
	Sched 20	16.000	15.376	0.312	52.32
	Standard	16.000	15.250	0.375	62.64
	X-Heavy	16.000	15.000	0.500	82.85

STEEL ROUND TUBE				
O.D. (Inches)	I.D. (Inches)	Wall Thickness		Weight per Foot (lbs)
		Ga.	Dec.	
1/2	3/8	16ga	0.065	0.30
3/4	5/8	16ga	0.065	0.48
	3/5	14ga	0.083	0.59
	1/2	11ga	0.120	0.81
7/8	3/4	16ga	0.065	0.56
1	7/8	16ga	0.065	0.65
	5/6	14ga	0.083	0.81
	7/9	12ga	0.109	1.04
	3/4	11ga	0.120	1.13
1-1/4	1-1/8	16ga	0.065	0.82
	1	14ga	0.083	1.04
	1	13ga	0.095	1.17
	1	11ga	0.120	1.45
1-1/2	1-3/8	16ga	0.065	1.00
	1-1/3	14ga	0.083	1.26
	1-1/3	13ga	0.095	1.43
	1-1/4	11ga	0.120	1.77
1-5/8	1-3/7	13ga	0.095	1.55
	1-2/5	11ga	0.120	1.93
1-3/4	1-3/5	14ga	0.083	1.48
	1-5/9	13ga	0.095	1.68
	1-5/7	11ga	0.012	2.09
2	1-7/8	16ga	0.065	1.34
	1-5/6	14ga	0.083	1.70
	1-3/4	11ga	0.120	2.41
2-3/8	2-1/5	14ga	0.083	2.03
2-1/2	2-1/3	14ga	0.083	2.12
	2-1/4	11ga	0.120	3.05
3	2-7/8	16ga	0.065	2.04
	2-5/6	14ga	0.083	2.59
	2-7/9	12ga	0.109	3.37
	2-3/4	11ga	0.120	3.69
3-1/2	3-1/4	11ga	0.125	4.51
4-1/2	4-1/4	11ga	0.120	5.61
5	4-3/4	11ga	0.120	6.25
5-1/2	5-1/4	11ga	0.120	6.90
6	5-7/9	12ga	0.109	6.61
	5-3/4	11ga	0.120	7.54
	5-5/8	3/16	0.188	11.67
8	7-7/9	12ga	0.109	9.19
10	9-7/9	12ga	0.109	11.51
12	11-7/9	12ga	0.109	13.34

ALUMINUM ROUND TUBE				
O.D. (Inches)	I.D. (Inches)	Wall Thickness		Weight per Foot (lbs)
		Ga.	Dec.	
1/2	1/4	11ga	0.120	0.02
1-1/2	1	1/4	0.250	1.16
2-1/2	2-3/8	16ga	0.065	0.59
4	3	1/2	0.500	6.47

STEEL SQUARE TUBING				
O.D. (Inches)	Wall Thickness		I.D. (Inches)	Weight per Foot (lbs)
	Ga.	Dec.		
1/2	16ga	0.065	3/8	0.385
3/4	16ga	0.065	5/8	0.606
	14ga	0.083	3/5	0.753
	11ga	0.120	1/2	1.030
1	16ga	0.065	7/8	0.827
	14ga	0.083	5/6	1.040
	11ga	0.120	3/4	1.840
1-1/4	16ga	0.065	1-1/8	1.050
	14ga	0.083	1	1.320
	11ga	0.120	1	1.440
	3/16	0.188	7/8	2.620
1-1/2	16ga	0.065	1-3/8	1.270
	14ga	0.083	1-1/3	1.600
	11ga	0.120	1-1/4	2.250
	3/16	0.188	1-1/8	3.230
	1/4	0.250	1	4.110
1-3/4	14ga	0.083	1-3/5	1.880
	11ga	0.120	1-1/2	2.660
2	16ga	0.065	1-7/8	1.710
	14ga	0.083	1-5/6	2.160
	11ga	0.120	1-3/4	3.070
	3/16	0.188	1-5/8	4.320
	1/4	0.250	1-1/2	5.410
2-1/2	11ga	0.120	2-1/4	3.880
	3/16	0.188	2-1/8	5.590
	1/4	0.250	2	7.110
3	14ga	0.083	2-5/6	3.290
	11ga	0.120	2-3/4	4.580
	3/16	0.188	2-5/8	6.870
	1/4	0.250	2-1/2	8.810
	5/16	0.313	2-3/8	10.580
3-1/2	3/8	0.375	2-1/4	12.170
	3/16	0.188	3-1/8	8.150
	1/4	0.250	3	10.510
4	11ga	0.120	3-3/4	6.220
	3/16	0.188	3-5/8	9.420
	1/4	0.250	3-1/2	12.210
	5/16	0.313	3-3/8	14.830
	3/8	0.375	3-1/4	17.270
	1/2	0.500	3	21.630

STEEL SQUARE TUBING				
O.D. (Inches)	Wall Thickness		I.D. (Inches)	Weight per Foot (lbs)
	Ga.	Dec.		
4-1/2	3/16	0.188	4-1/8	10.700
	1/4	0.250	4	13.910
5	3/16	0.188	4-5/8	11.970
	1/4	0.250	4-1/2	15.620
	3/8	0.375	4-1/4	22.370
	1/2	0.500	4	28.430
6	3/16	0.188	5-5/8	14.530
	1/4	0.250	5-1/2	19.020
	5/16	0.313	5-3/8	23.340
	3/8	0.375	5-1/4	27.480
7	1/2	0.500	5	35.240
	1/4	0.250	6-1/2	22.420
	1/2	0.500	6	42.050
8	3/16	0.188	7-5/8	19.630
	1/4	0.250	7-1/2	25.820
	3/8	0.375	7-1/4	37.690
	1/2	0.500	7	48.850
10	1/4	0.250	9-1/2	32.630
	3/8	0.375	9-1/4	47.900
	1/2	0.500	9	62.460
12				
	1/4	0.250	11-1/2	39.430

**ALUMINUM SQUARE TUBING**

O.D. (Inches)	Wall Thickness		I.D. (Inches)	Weight per Foot (lbs)
	Ga.	Dec.		
3/4	11ga	0.120	1/2	0.364
1	16ga	0.065	7/8	0.271
	11ga	0.120	3/4	0.526
1-1/4	11ga	0.120	1	0.655
1-1/2	11ga	0.120	1-1/4	0.825
	1/4	0.250	1	1.500
2	11ga	0.120	1-3/4	1.091
	1/4	0.250	1-1/2	2.100
3	11ga	0.120	2-3/4	1.673
	1/4	0.250	2	3.340
4	11ga	0.120	3-3/4	2.324
	1/4	0.250	3-1/2	4.365

**STAINLESS SQUARE TUBING**

O.D. (Inches)	Wall Thickness		I.D. (Inches)	Weight per Foot (lbs)
	Ga.	Dec.		
3/4	11ga	0.120	1/2	0.810
1	16ga	0.065	7/8	0.830
	11ga	0.120	3/4	1.436
1-1/4	11ga	0.120	1	1.840
1-1/2	11ga	0.120	1-1/4	2.252
2	11ga	0.120	1-3/4	3.068
	3/16	0.188	1-5/8	4.460
	1/4	0.250	1-1/2	6.010
3	11ga	0.120	2-3/4	4.700
	3/16	0.188	2-5/8	6.903
	1/4	0.250	2	8.953
4	11ga	0.120	3-3/4	6.260
	1/4	0.250	3-1/2	12.680

STEEL RECTANGULAR TUBING				
O.D. (Inches)		Wall Thickness		Weight per Foot (lbs)
Length	Width	Ga.	Dec.	
1/2	1	16ga	0.063	0.610
1/2	1-1/2	16ga	0.063	0.827
3/4	1-1/2	14ga	0.083	1.180
1	1-1/2	16ga	0.063	1.050
		14ga	0.083	1.320
		11ga	0.120	1.840
1	2	16ga	0.063	1.270
		14ga	0.083	1.600
		11ga	0.125	2.760
		3/16	0.188	3.340
1	3	14ga	0.083	2.160
		11ga	0.120	3.070
		3/16	0.188	4.330
1-1/4	2-1/2	14ga	0.083	2.020
1-1/2	2	11ga	0.120	2.660
		3/16	0.188	4.080
1-1/2	2-1/2	11ga	1.250	3.120
		3/16	0.188	4.430
		1/4	0.250	5.590
1-1/2	3	14ga	0.083	2.450
		11ga	0.120	3.450
		3/16	0.188	4.960
		1/4	0.250	6.800
2	3	14ga	0.083	2.730
		11ga	0.120	3.760
		3/16	0.188	5.590
		1/4	0.250	8.810
2	4	14ga	0.083	3.290
		11ga	0.120	4.580
		3/16	0.188	6.870
		1/4	0.250	8.810
		3/8	0.375	12.700
2	5	11ga	0.125	5.610
		3/16	0.188	8.150
		1/4	0.250	12.210
2	6	11ga	0.125	6.460
		3/16	0.188	9.420
		1/4	0.250	12.210
2	8	3/16	0.188	11.970
		1/4	0.250	15.620
		3/8	0.375	22.370

STEEL RECTANGULAR TUBING				
O.D. (Inches)		Wall Thickness		Weight per Foot (lbs)
Length	Width	Ga.	Dec.	
2-1/2	3	1/4	0.250	8.500
2-1/2	3-1/2	1/4	0.250	8.500
2-1/2	5	1/4	0.250	11.350
		11ga	0.120	5.520
		3/16	0.188	8.150
		1/4	0.250	10.510
3	4	3/8	0.375	14.710
		3/16	0.188	9.420
		1/4	0.250	12.210
		5/16	0.313	14.830
		3/8	0.375	17.270
3	6	3/16	0.188	10.700
		1/4	0.250	13.910
		3/8	0.375	19.820
3	8	3/16	0.188	13.250
		1/4	0.250	17.320
		3/8	0.375	24.930
4	5	3/16	0.188	10.700
		1/4	0.250	13.910
4	6	3/16	0.188	11.970
		1/4	0.250	15.620
		3/8	0.375	22.370
4	7	1/4	0.250	17.320
		3/16	0.188	14.530
		1/4	0.250	19.020
		3/8	0.375	27.480
4	8	1/2	0.500	35.240
		3/16	0.188	17.080
		1/4	0.250	22.420
4	10	3/8	0.375	37.690
		1/4	0.250	19.020
		3/8	0.375	27.480
5	7	1/4	0.250	19.020
		3/8	0.375	27.480
		1/2	0.500	35.240
6	8	3/16	0.188	17.080
		1/4	0.250	22.420
		3/8	0.375	32.580
6	10	1/2	0.500	42.050
		1/4	0.250	25.820
		3/8	0.375	37.690
		1/2	0.500	48.850

STEEL RECTANGULAR TUBING				
O.D. (Inches)		Wall Thickness		Weight per Foot (lbs)
Length	Width	Ga.	Dec.	
6	12	1/4	0.250	29.230
		1/4	0.250	29.230
8	10	3/16	0.188	22.180
		1/4	0.250	29.230
		3/8	0.375	42.790
8	12	1/4	0.250	32.630
		3/8	0.375	47.900

ALUMINUM RECTANGULAR TUBING				
O.D. (Inches)		Wall Thickness		Weight per Foot (lbs)
Length	Width	Ga.	Dec.	
1/2	1	11ga	0.120	0.360
1	1-1/2	11ga	1.200	0.650
1	2	11ga	0.125	0.800
1	3	11ga	0.120	1.090
1-1/2	2	11ga	0.120	0.950
1-1/2	3	11ga	1.200	1.270
2	3	11ga	0.120	1.400
		1/4	0.250	2.700
2	4	1/4	0.250	3.200
		11ga	0.125	2.030
2	5	1/4	0.250	3.900
		11ga	0.125	2.300
2	6	1/4	0.250	4.410
		11ga	0.120	2.030
3	4	1/4	0.250	3.800
		11ga	0.120	2.030
4	6	3/16	0.188	4.260

STAINLESS RECTANGULAR TUBING				
O.D. (Inches)		Wall Thickness		Weight per Foot (lbs)
Length	Width	Ga.	Dec.	
1	2	11ga	0.125	2.250
1-1/2	3	11ga	1.200	3.480
2	3	3/16	0.188	5.700
		11ga	0.125	2.250
2	4	3/16	0.188	6.900

**STEEL SHEETS (HOT ROLL)**

Thickness (ga)	Decimal Avg	Sheet Size		Weight per sq. foot	Weight per sheet
		Width	Length		
10ga	0.135	48	96	5.625	180.00
		48	120	5.625	225.00
		48	144	5.625	270.00
		60	96	5.625	225.00
		60	120	5.625	281.25
		60	144	5.625	337.50
		72	96	5.625	270.00
		72	120	5.625	337.50
		72	144	5.625	405.00
11ga	0.120	48	96	5.000	160.00
		48	120	5.000	200.00
		48	144	5.000	240.00
		60	96	5.000	200.00
		60	120	5.000	250.00
		60	144	5.000	300.00
		72	120	5.000	300.00
12ga	0.109	48	96	4.375	140.00
		48	120	4.375	175.00
		48	144	4.375	210.00
		48	156	4.375	227.50
		60	96	4.375	175.00
		60	120	4.375	218.75
		60	144	4.375	262.50
		72	96	4.375	210.00
		72	120	4.375	262.50
		72	144	4.375	315.00
		72	156	4.375	341.25
14ga	0.083	48	96	3.125	100.00
		48	120	3.125	125.00
		48	144	3.125	150.00
		60	96	3.125	125.00
		60	120	3.125	156.25
		60	144	3.125	187.50
		72	96	3.125	150.00
		72	120	3.125	187.50
		72	144	3.125	225.00
16ga	0.063	48	96	2.500	80.00
		48	120	2.500	100.00
		48	144	2.500	120.00
		60	96	2.500	100.00

**STEEL SHEETS (COLD ROLL)**

Thickness (ga)	Decimal Avg	Sheet Size		Weight per sq. foot	Weight per sheet
		Width	Length		
18ga	0.050	48	96	2.000	64.00
		48	120	2.000	80.00
		60	120	2.000	100.00
20ga	0.038	48	96	1.500	48.00
		48	120	1.500	60.00
22ga	0.031	48	120	1.250	50.00
24ga	0.025	48	120	1.000	40.00

**STEEL PLATES (HOT ROLL)**

Thickness (in.)	Decimal Avg	Sheet Size		Weight per sq. foot	Weight per sheet
		Width	Length		
3/16	0.188	48	96	7.66	245.12
		48	120	7.66	306.40
		48	144	7.66	367.68
		48	156	7.66	398.32
		60	96	7.66	306.40
		60	120	7.66	383.00
		60	144	7.66	459.60
		72	96	7.66	367.68
		72	120	7.66	459.60
		72	144	7.66	551.52
		72	156	7.66	597.48
				96	240
1/4	0.250	48	96	10.21	326.72
		48	120	10.21	408.40
		48	144	10.21	490.08
		60	96	10.21	408.40
		60	120	10.21	510.50
		60	144	10.21	612.60
		72	96	10.21	490.08
		72	120	10.21	612.60
		72	144	10.21	735.12
		96	117	10.21	796.38
		96	240	10.21	1633.60
		5/16	0.312	48	96
48	120			12.75	510.00
60	120			12.75	637.50
3/8	0.375	48	96	15.32	490.24
		48	120	15.32	612.80
		48	144	15.32	735.36
		60	96	15.32	612.80
		60	120	15.32	766.00
		60	144	15.32	919.20
		72	96	15.32	735.36
		72	120	15.32	919.20
		72	144	15.32	1103.04
		96	240	15.32	2451.20

**STEEL PLATES (HOT ROLL)**

Thickness (in.)	Decimal Avg	Sheet Size		Weight per sq. foot	Weight per sheet
		Width	Length		
1/2	0.500	48	96	20.42	653.44
		48	120	20.42	816.80
		60	120	20.42	1021.00
		72	120	20.42	1225.20
		48	144	20.42	980.16
		60	144	20.42	1225.20
		72	144	20.42	1470.24
		96	240	20.42	3267.20
5/8	0.625	96	240	25.50	4080.00
3/4	0.750	48	96	30.63	980.16
		96	240	30.63	4900.80
1	1.000	48	96	40.84	1306.88
		60	120	40.84	2042.00
		96	240	40.84	6534.40
1-1/4	1.250	96	240	51.05	8168.00
1-1/2	1.500	48	96	61.26	1960.32
		96	240	61.26	9801.60
1-3/4	1.750	48	96	71.47	2287.04
		96	240	71.47	11435.20
2	2.000	96	240	81.68	13068.80
2-1/2	2.500	96	240	102.10	16336.00
2-3/4	2.750	96	240	112.31	17969.60
3	3.000	96	240	122.52	19603.20
4	4.000	96	240	163.35	26136.00
6	6.000	48	96	245.04	7841.28

ALUMINUM SHEETS/PLATES (SMOOTH MILL FINISH)					
Thickness (ga)	Decimal Avg	Sheet Size		Weight per sq. foot	Weight per sheet
		Width	Length		
16ga	0.063	48	120	0.898	35.92
		60	120	0.898	44.90
13ga	0.090	48	96	1.287	41.18
		48	120	1.287	51.48
		60	120	1.287	64.35
11ga	0.125	48	96	1.782	57.02
		48	120	1.782	71.28
		60	120	1.782	89.10
3/16	0.190	48	96	2.714	86.85
		48	120	2.714	108.57
		60	120	2.714	135.71
1/4	0.250	48	96	3.564	114.05
3/8	0.375	48	96	5.390	172.48
1/2	0.500	48	96	7.210	230.72
3/4	0.750	48	144	10.820	519.36
1	1.000	48	96	14.444	462.20

## STAINLESS SHEETS/PLATES

Thickness (ga)	Decimal Avg	Sheet Size		Weight per sq. foot	Weight per sheet
		Width	Length		
10ga	0.135	48	96	5.670	181.44
		60	120	5.670	283.50
11ga	0.120	48	96	5.040	161.28
		48	120	5.040	201.60
		60	120	5.040	252.00
12ga	0.109	48	96	4.410	141.12
		48	120	4.410	176.40
		48	144	4.410	211.68
		60	120	4.410	220.50
		60	144	4.410	264.60
14ga	0.083	48	96	3.154	100.93
		48	120	3.154	126.16
		60	120	3.154	157.70
16ga	0.063	48	96	2.520	80.64
		60	120	2.520	126.00
18ga	0.050	48	96	2.016	64.51
		48	120	2.016	80.64
20ga	0.038	48	120	1.512	60.48
22ga	0.031	48	96	1.260	40.32
		48	120	1.260	50.40
24ga	0.025	48	120	1.008	40.32
3/16	0.187	48	96	8.575	274.40
		48	120	8.575	343.00
1/4	0.250	48	96	11.160	357.12
		48	120	11.160	446.40
5/16	0.313	48	120	13.746	549.84
3/8	0.375	48	96	16.500	528.00
1/2	0.500	48	96	21.660	693.12

**GALVANIZED SHEETS**

Thickness (ga)	Decimal Avg	Sheet Size		Weight per sq. foot	Weight per sheet
		Width	Length		
10ga	0.135	48	96	5.781	184.99
		48	120	5.781	231.24
11ga	0.120	48	144	5.156	247.49
12ga	0.109	48	96	4.531	144.99
		48	120	4.531	181.24
		48	144	4.531	217.49
		60	96	4.531	181.24
14ga	0.083	48	96	3.281	104.99
		48	120	3.281	131.24
16ga	0.063	48	96	2.656	84.99
		48	120	2.656	106.24
		60	120	2.656	132.80
18ga	0.050	48	96	2.156	68.99
		48	120	2.156	86.24
		60	120	2.156	107.80
20ga	0.038	48	96	1.656	52.99
		48	120	1.656	66.24
		60	120	1.656	82.80
22ga	0.031	48	96	1.406	44.99
		48	120	1.406	56.24
24ga	0.025	48	120	1.156	46.24
		60	120	1.156	57.80
26ga	0.019	48	120	0.906	36.24

**STEEL TREAD/FLOOR PLATE**

Thickness (in.)	Decimal Avg	Sheet Size		Weight per sq. foot	Weight per sheet
		Width	Length		
14ga	0.083	48	96	3.75	120.00
		48	120	3.75	150.00
11ga	0.120	48	96	6.15	196.80
		48	120	6.15	246.00
		60	120	6.15	307.50
3/16	0.188	48	96	8.71	278.72
		48	120	8.71	348.40
		60	120	8.71	435.50
1/4	0.250	48	96	11.25	360.00
		48	120	11.25	450.00
		48	144	11.25	540.00
		60	120	11.25	562.50
		60	144	11.25	675.00
3/8	0.375	48	96	16.37	523.84
		48	120	16.37	654.80
		60	120	16.37	818.50
1/2	0.500	48	96	21.47	687.04
		48	120	21.47	858.80
		60	120	21.47	1073.50

**ALUMINUM TREAD/FLOOR PLATE**

Thickness (ga)	Decimal Avg	Sheet Size		Weight per sq. foot	Weight per sheet
		Width	Length		
16ga	0.063	48	120	1.008	40.32
11ga	0.125	48	96	1.932	61.82
		48	120	1.932	77.28
		60	120	1.932	96.60
3/16	0.190	48	96	3.000	96.00
1/4	0.250	48	96	3.900	124.80

**WELDED & WOVEN WIRE**

Size (Inches)		Sheet Size		Weight per sq. foot	Weight per sheet	Type
Rod	Opening	Width	Length			
1/8	1/2	48	120	1.51	60.40	Woven wire
1/4	2-1/4	48	120	1.80	72.00	Woven wire
1/8	1	48	120	0.96	38.40	Welded wire
1/4	2	48	120	1.80	72.00	Welded wire

**PERFORATED STEEL SHEET**

Size (Inches)		Thickness		Sheet Size		Weight per sq. foot	Weight per sheet	Pattern Type
Hole Diameter	Distance	Ga.	Dec.	Width	Length			
1/4	1	20ga	0.038	48	120	1.41	56.50	Straight
1/8	3/16	16ga	0.063	48	120	1.36	54.44	Stg
1/4	3/8	16ga	0.063	48	120	1.50	60.00	Stg
1/2	11/16	16ga	0.063	48	120	2.00	80.00	Stg
1/4	3/8	14ga	0.083	48	120	2.00	80.00	Stg
1/2	11/16	14ga	0.083	48	120	1.65	66.00	Stg
1/8	3/16	11ga	0.125	48	120	3.00	120.00	Stg
1/4	3/8	11ga	0.125	48	120	3.00	120.00	Stg
1/2	11/16	11ga	0.125	48	120	2.65	106.00	Stg
1/4	3/8	3/16	0.188	48	120	4.60	184.00	Stg
1/4	3/8	1/4	0.250	48	120	6.00	240.00	Stg
3/8	9/16	1/4	0.250	48	120	6.10	244.00	Stg
1/8	3/16	14ga	0.083	48	120	2.00	80.00	Stg

**REWIRE SHEETS**

Opening Size	Thickness		Sheet Size		Weight per sq. foot	Weight per sheet
	Ga.	Dec.	Width	Length		
6 x 6	6ga	0.203	96	240	0.42	67.20

**REBAR**

Size (inches)		Weight per Foot (lbs)	Weight per Stick (lbs)
#	Diameter		
#3	3/8	0.38	7.52
#4	1/2	0.67	13.36
#5	5/8	1.04	20.86
#6	3/4	1.50	30.04
#7	7/8	2.04	40.88
#8	1	2.67	53.40
#10	1-1/4	4.30	86.06

### BAR GRATING

Bar Size (inches)			Sheet Size		Weight per sq. foot	Type
Thick-ness	Width	Width	Length			
1/8	x	1	36	240	5.10	Flat Steel
1/8	x	1	36	240	5.36	Flat Galvanized
3/16	x	1	36	240	7.30	Flat Steel
3/16	x	1	36	240	7.30	Serated Steel
3/16	x	1	36	240	7.30	Flat Galvanized
3/16	x	1	36	240	7.30	Serated Galvanized
3/16	x	1-1/4	36	240	8.90	Flat Steel
3/16	x	1-1/4	36	240	8.90	Serated Steel
3/16	x	1-1/4	36	240	8.90	Flat Galvanized
3/16	x	1-1/2	36	240	10.60	Flat Steel
3/16	x	1-1/2	36	240	10.60	Serated Steel
3/16	x	1-1/2	36	240	10.60	Flat Galvanized

### GRIP STRUT

Size (Inches)		Thickness		Weight per Foot (lbs)	Type
Width	Height	Ga.	Dec.		
7	1-1/2	14ga	0.083	3.000	Galvanized
9-1/2	1-1/2	14ga	0.083	3.600	Galvanized
11-3/4	1-1/2	14ga	0.083	4.000	Galvanized
18-3/4	1-1/2	14ga	0.083	6.100	Galvanized
24	2	12ga	0.109	10.400	Galvanized